- (Original) The wall structure as set forth in Claim 1 including a plate disposed on each of said footings for supporting an end of said lintel.
- 3. (Currently Amended) The wall structure as set forth in Claim 1 wherein including a post extending from each of said footings, said at least one further tensioning rod extending upwardly into said post; each of said post posts includes including a vertical slot for receiving an end of said wall.
- (Original) The wall structure as set forth in Claim 3 including a plate disposed on each of said footings for supporting said post and said lintel.
- (Currently Amended) The wall structure as set forth in Claim 3 [[4]]
 wherein an end of each of said lintels lintel extends into said slot of each of adjacent
 ones of said posts said posts.
- 6. (Currently Amended) The wall structure as set forth in Claim 3 including at least one rebar disposed longitudinally within each of said lintels lintel and grout for imbedding said rebar within said lintel and a lower end of at least one of said tensioning rods rod within said lintel.
- (Original) The wall structure as set forth in Claim 1 wherein said lintel is generally C-shaped in cross section.

- (Currently Amended) The wall structure as set forth in Claim 1 [[7]]
 wherein said lintel includes a longitudinally oriented upwardly facing opening.
- (Original) The wall structure as set forth in Claim 8 wherein at least one of said tensioning rods extend upwardly through said opening.

10-16. (Cancelled)

- (Currently Amended) The wall structure as set forth in Claim 1 wherein said plurality of courses comprise concrete masonry units.
- 18. **(Currently Amended)** The wall structure as set forth in Claim 1 wherein said <u>plurality of courses comprise bricks having at least one passageway therethrough.</u>

19-22. (Cancelled)

- 23. (Currently Amended) A method for constructing an above ground wall having a plurality of wall sections, said method comprising in combination:
- a) developing a footing at least partially in the ground at each end of the wall sections of the wall to be built;
 - b) installing at least one tension rod to extend upwardly from each

footing;

- c) placing a plate on each footing;
- d) building a post on each plate with blocks to provide a vertical cavity for receiving <u>said</u> the at least one tensioning rod and to provide a vertical slot for receiving an end of the wall section to be built;
- e) placing a lintel on each of the plates to locate the ends of the lintel in the slots of the respective posts and above ground <u>for supporting a wall section</u>;
- f) laying a plurality of courses upon the lintel to define the wall section, each of the courses extending into the slots of the respective one of the posts; and
- g) installing a plurality of tensioning rods extending from within the lintel upwardly into the wall <u>section in conjunction with</u> during exercise of said step of laying.
- 24. (Original) The method as set forth in Claim 23 wherein said step of laying includes the step of laying concrete masonry units.
- 25. (Original) The method as set forth in Claim 23 wherein said step of laying includes the step of laying bricks.
- (Currently Amended) A wall structure having an above ground wall, said wall structure comprising in combination:
- a) a plurality of footings disposed at least partially in the ground at each end of said wall:

- b) said wall including a lintel, each end of said lintel being supported above ground on adjacent ones of receiving support at each end from said footings and a plurality of courses extending upwardly from [[form]] said lintel;
- c) at least one <u>tensioning</u> rod extending upwardly from said lintel into said wall;
- d) a post extending from a respective one of said plurality of footings for supporting an end of said wall, said post including a vertical slot for receiving the corresponding end of said wall; and
- e) at least one further <u>tensioning</u> rod extending upwardly from within each [[a]] respective one of said plurality of footings into the respective one of said posts and adapted for resisting tilting of said post.
- 27. (Original) The wall structure as set forth in Claim 26 including a starter course disposed on the respective one of said plurality of footings for supporting an end of said lintel.
- 28. (Currently Amended) The wall structure as set forth in Claim 26 including at least one rebar disposed longitudinally within said lintel and grout for imbedding said rebar and a lower end of said tensioning rod within said lintel.
- 29. (Original) The wall structure as set forth in Claim 26 wherein said lintel is generally C-shaped in cross section.

- (Currently Amended) The wall structure as set forth in Claim <u>26</u> [[29]]
 wherein said lintel includes a longitudinally oriented upwardly facing opening.
- (Currently Amended) The wall structure as set forth in Claim 30
 wherein each of said tensioning rods extends extend upwardly through said opening.
- 32. (Currently Amended) A method for constructing an above ground wall, said method comprising in combination:
- a) developing a footing at least partially in the ground at each end of the wall to be built;
- b) installing at least one <u>tensioning</u> rod to extend upwardly from each footing;
- c) building a post on each footing with blocks to provide a vertical cavity for receiving the at least one <u>tensioning</u> rod and to provide a vertical slot for receiving an end of the wall to be built:
- d) locating the ends of a lintel in the slots of the respective posts and upon the footings to locate the lintel above ground;
- e) laying a plurality of courses upon the lintel, each of the courses extending into the slots of the respective one of the posts; and
- f) installing a plurality of <u>tensioning</u> rods extending from within the lintel upwardly into the wall <u>in conjunction with during</u> exercise of said step of laying.

- 33. (Original) The method as set forth in Claim 32 wherein said step of laying includes the step of laying concrete masonry units.
- 34. (Original) The method as set forth in Claim 32 wherein said step of laying includes the step of laying bricks.
- 35. (New) The method as set forth in Claim 32 wherein said step of building includes the step of laying blocks.